ISO9001: 2015

ISO14001: 2015

APPROVAL SPECIFICATIONS

Title. FPC Connector

Product Model. GYFA0515-XXRD-G

Customer's Part NO.

Customer's Model:

Customer's Approval Requested.

Please return this copy as a certification of your approval.

Checked by: Date:

Approved by: Date:

Swiclick

Address:Rm. D1/25F,No 2070,Electronical Technology Building-C,Shennan Mid-road,Futian Dist.,Shenzhen,China.

Website:https://www.swiclick.com

Swiclick

APPROVAL SPECIFICATIONS

Product name	P/N	Version	Document No.	Page
FPC Connector	GYFA0515-XXRD-G	A/00		2/13

变更履历表：

版本	变更记录	变更人	变 更 日 期

Swiclick

APPROVAL SPECIFICATIONS

Product name	P/N	Version	Document No.	Page
FPC Connector	GYFA0515-XXRD-G	A/00		3/13

1、 概述

GENERAL

1.1 适用范围

This specification covers the requirements for product performance and test methods of the FPC Connector.， Product shall be of the design, construction and physical dimensions specified in the applicable product drawing.

此份规格书包含了对 FPC 连接器产品测试方法及产品特性的要求 ，产品设计开发及图面上的尺寸均应参照此规格书。

1.2 工作温度范围

Operating Temperature Range

-25℃～85℃(在标准大气压、标准湿度条件下)

-25℃～85℃(Normal humidity, normal air pressure)

1.3 相对湿度： ≤85%

Operating Relative Humidity: ≤85%

1.4 实验条件：若没有特别说明，则试验大气条件如下：

Test Conditions: Unless otherwise specified, the atmospheric conditions for making measurements and tests are as follows:

环境温度： 20~35℃

Ambient Temperature: 20~35℃

相对湿度： 25~85%

Relative Humidity: 25~85%

大气压力： 86~106Kpa (860~106mbar)

Air Pressure: 86~106Kpa (860~106mbar)

1.5 保质期

Quality guarantee

产品出货后在温度-5℃～35℃ 、湿度 25%～85%条件下，确保未开封状态保质期为 3 个月；

保管时尤其应注意避开高湿高温和有腐蚀性气体的环境

Stored at a condition of temperature -5℃～35℃,humidity 25%～85% and ensure that it be unsealed after delivery, it can be stored for 3 months.

Should especially avoid the environment of high humidity and corrosive gases

1.6、命名规则

Naming rules

PART NO.： **GYFA 05 15 - XX RD - G**

1 2 3 4 5 6

1	Series name	FPC Connector
2	Pitch between	0.5 mm Pitch
3	Height	1.5mm
4	Number of contacts	04~60
5	Assembly style	Right Angle /Low Contact SMT Type
6	Plating	Gold flash over Nickel

Swiclick

APPROVAL SPECIFICATIONS

Product name	P/N	Version	Document No.	Page
FPC Connector	GYFA0515-XXRD-G	A/00		4/13

2、 详细说明

Detailed specification

2.1 外观：应无影响、降低产品性能的缺陷；

Appearance: There should be no defects that affect the serviceability of product.

2.2 结构尺寸和安装尺寸：应符合装配图要求；

Style and dimension: shall conform to the assemble drawings.

2.3 标识： 参见产品图纸

Markings: Refer to individual product drawing.

2.4 操作形式：有触觉反应的操作

Type of actuating: Tactile feedback.

2.5 开关工作额定值： 50V AC/DC 0.5A

Ratings：50V AC/DC 0.5A

3．电气性能：

ELECTRICAL SPECIFICATION

项 目 ITEM		试 验 条 件 TEST CONDITIONS	要求 REQUIREMENTS
3.1	接触电阻 Contact Resistance	将样品与适合之 FPC 连接，测试电压 20mV，限电流 10mA 下进行阻抗测试。 (JIS C5402 5.4) Mate applicable FPC and measure by dry circuit, 20mV Max, 10mA. (JIS C5402 5.4)	≤40mΩ
3.2	绝缘电阻 Insulation Resistance	将样品与适合之 FPC 连接，提供相邻端子间测试电压 500V DC 进行绝缘阻抗测试。 (JIS C5402 5.2 / MIL-STD-202 Method 302) Mate applicable FPC and apply 500V DC between adjacent terminal or ground. (JIS C5402 5.2 / MIL-STD-202 Method 302)	≥50MΩ
3.3	介质耐压 Dielectric voltage proof	将样品与适合之 FPC 连接，相邻端子间需可承受 250V AC 1 分钟。 Mate applicable FPC, apply 250V AC(rms) for 1 minute between adjacent terminal or ground. (JIS C5402 5.1 / MIL-STD-202 Method 301)	无击穿 There should be no breakdown

Swiclick

APPROVAL SPECIFICATIONS

Product name	P/N	Version	Document No.	Page
FPC Connector	GYFA0515-XXRD-G	A/00		5/13

	项目 ITEM	试 验 条 件 TEST CONDITIONS	要求 REQUIREMENTS
4．机械性能： MECHANICAL SPECIFICATION			
4.1	FPC 保持力 FPC Retention Force	将盖子盖上，与 FPC 连接，以操作速度每分钟位移 25±3mm 进行 FPC 保持力测试。 Insert the actuator, pull the FPC at a rate of 25±3mm per minute.	Pos. x 0.15N Min.
4.2	端子保持力 Terminal Retention Force	端子与 Housing 组装后，以操作速度每分钟位移 25±3mm 将端子拔出 Housing，进行端子保持力测试。 Apply axial pull out force at the rate of 25±3 mm/minute on the terminal assembled in the housing.	Pos. x 0.8N Min.
4.3	盖子往返操作测试 Repeated Actuator Insertion/ Withdrawal	将盖子与 FPC 反复连接，以每分钟小于 10 cycles 连续操作 20 次。 Insert and withdraw actuator up to 20 cycles at the speed rate of less than 10 cycles/minute.	接触电阻：60mΩ 以下 Contact Resistance：60 mΩ Max
4.4	温升 Temperature Rise	量测通过 FPC 最大容许电流时，样品接触点之温升。(UL498) Mate applicable FPC and measure the temperature rise of contact when the maximum AC rated current is passed. (UL498)	温升：30° C 以下 Temperature rise：30°C Max
4.5	耐冲击性 Shock	测试速度 490m/s² 持续时间 11msX、Y、Z、3 个轴 6 各方向各 3 次 FPC 嵌合状态下测试。 Mate applicable FPC and subject to the following shock conditions. With acceleration 490m/s² lasting 11ms, 3times of shocks shall be applied for each 6 directions along 3 mutually perpendicular axes	外观：目视外观无任何 损坏异状； 瞬间断电：1 μsec 以下 Appearance：No Damage Discontinuity：1 μsec Max
4.	耐振性 Vibration	频率 10-55-10Hz，震幅 1.52mm，转换时间 1 分钟传递。X/Y/Z 方向各 2 小时，共计 6 小时 FPC 嵌合状态下测试 Mate connectors and subject to the following vibration conditions, for period of 2 hours in each of 3 mutually perpendicular axes. Amplitude: 1.52mm Frequency: 10~55~10Hz in 1 minutes	外观：目视外观无任何 损坏异状； 瞬间断电：1 μsec 以下 Appearance：No Damage Discontinuity：1 μsec Max

Swiclick

APPROVAL SPECIFICATIONS

Product name	P/N	Version	Document No.	Page
FPC Connector	GYFA0515-XXRD-G	A/00		6/13

5、环境耐久性：
ENVIRONMENTAL SPECIFICATION

项目 ITEM		试 验 条 件 TEST CONDITIONS	要求 REQUIREMENTS
5.1	耐热性 Heat Resistance	85±2℃条件下 放置 96 小时，然后在常温常湿下放置 1 小时后测试 FPC 嵌合状态下测试 Mate applicable FPC and expose to 85 ± 2 ℃ for 96H, Upon completion of the exposure period, the test specimens shall be conditioned at ambient room conditions for 1H, after which the specified measurements shall be performed. (JIS C0021 / MIL-STD-202 Method 108)	外观：目视外观无任何 损坏异状； 接触电阻：60mΩ 以下 Appearance：No Damage Contact Resistance：60 mΩ Max
5.2	耐寒性 Cold Resistance	将样品与适合之 FPC 连接，置于环境温度 -25±2° C， 测试时间 96 小时，再置放于室温下 1~2 小时。 (JIS C0020) Mate applicable FPC and expose to -25±2°C for 96 hours. Upon completion of the exposure period, the test specimens shall be conditioned at ambient room conditions for 1 to 2 hours, after which the specified measurements shall be performed.(JIS C0020)	外观：目视外观无任何 损坏异状； 接触电阻：60mΩ 以下 Appearance：No Damage Contact Resistance：60 mΩ Max
5.3	耐湿性 Humidity	将样品与适合之 FPC 连接，置于环境温度 60±2° C， 相对湿度 90~95%，测试时间 96 小时，再置放于室温 下 1~2 小时。 (JIS C0022 / MIL-STD-202 Method 103) Mate applicable FPC and expose to 60 ± 2°C, relative humidity 90 to 95% for 96 hours. Upon completion of the exposure period, the test specimens shall be conditioned at ambient room conditions for 1 to 2 hours, after which the specified measurements shall be performed. (JIS C0022 / MIL-STD-202 Method 103)	外观：目视外观无任何 损坏异状； 接触电阻：60mΩ 以下 Appearance：No Damage Contact Resistance：60 mΩ Max

Swiclick

APPROVAL SPECIFICATIONS

Product name	P/N	Version	Document No.	Page
FPC Connector	GYFA0515-XXRD-G	A/00		7/13

项目 ITEM		试 验 条 件 TEST CONDITIONS	要求 REQUIREMENTS
5.4	冷热冲击 Temperature Cycling	将样品与适合之 FPC 连接，承受 5 cycles 冷热冲击后， 置放于室温下 1~2 小时。 1 cycle time 如下 a) -55±3° C 30 分钟 b) +85±3° C 30 分钟 (JIS C0025) Mate applicable FPC and subject to the following conditions for 5 cycles. Upon completion of the exposure period, the test specimens shall be conditioned at ambient room conditions for 1 to 2 hours, after which the specified measurements shall be performed. 1 cycle a) -55±3°C 30minutes b) +85±3°C 30minutes (Transit time shall be with in 3 minutes) (JIS C0025)	外观：目视外观无任何 损坏异状； 接触电阻：60mΩ 以下 Appearance：No Damage Contact Resistance：60 mΩ Max
5.5	盐水喷雾 Salt Spray	将样品与适合之 FPC 连接，使用 5±1%浓度盐水，测试温度 35±2° C，测试时间 24±1 小时,后于室温下使用清水 冲洗后再干燥。 (JIS C0023 / MIL-STD-202 Method 101) Mate applicable FPC and expose to the following salt mist conditions. Upon completion of the exposure period, salt deposits shall be removed by a gentle wash or dip in running water, after which the specified NaCl solution Concentration : 5 ± 1% Spray time : 24 ± 1 hours Ambient temperature : 35 ± 2°C (JIS C0023 / MIL-STD-202 Method 101)	外观：目视外观无任何 损坏异状； 接触电阻：60mΩ 以下 Appearance：No Damage Contact Resistance：60 mΩ Max
6．耐焊接热： SOLDERING CONDITIONS:			
6.1	可焊接性 Solderability	将焊锡部分浸入温度为 245℃±5℃的锡炉中 保持 3 秒 Dip soldering tail into Tin oven, temperature of Tin oven is 245℃±5℃. the test specimens shall be lasted 3sec.	焊接端应容易被熔融焊料润湿,粘锡面积应占浸入面积的 90%以上 Soldering tail shall be easy wetting by melted tin, Tin shall cover over 90% of dipping area of soldering leg

Swiclick

APPROVAL SPECIFICATIONS

Product name	P/N	Version	Document No.	Page
FPC Connector	GYFA0515-XXRD-G	A/00		8/13

项目 ITEM		试 验 条 件 TEST CONDITIONS	要求 REQUIREMENTS
6.2	回流焊时 Conditions for reflow	 NOTE: Please check the re-flow soldering condition by your own devices beforehand . Because the condition changes by the soldering devices, p.c. boards, and so on.	

注意事项(Notes):

a、印刷基板的焊盘尺寸参见产品图。

The pad size of the printed substrate is shown in the product diagram.

b、在使用烙铁的情况下，焊锡温度应在 350℃以下、3 秒以内。

In the case of using soldering iron, soldering conditions shall be 350℃ max and 3 sec.max.

c、防止助焊剂从开关的顶端渗入

Prevent flux penetration from the top of the switch

d、开关浸焊后，注意不要用溶剂或类似品清洗开关。

After switches were soldered,please be careful not to clean switches with solvent or other similar products.

e、浸焊后，注意不要在顶部施加负荷。

Right after switches were soldered;please be careful not to load to on the knobs of switches.

f、注意不要施加超负荷的压力或晃动开关。

Please be cautions not to give excessive static load or shock to switches.

g、开关浸焊后，印刷基板注意不要叠放。

Please be careful not to pile up P.W.B.after switches were soldered







NOTES:
1. MATERIAL:
   HOUSING: LCP, UL 94-V0, COLOR:NATURAL
   COVER: LCP, UL 94-V0, COLOR:BLACK;
   CONTACT: PHOSPHOR BRONZE
   LEG: PHOSPHOR BRONZE
2. PLATING:
   CONTACT: GOLD FLASH
   LEG: TIN OVER NICKEL





PIN NO.	DIM.A	DIM.B	DIM.C	PIN NO.	DIM.A	DIM.B	DIM.C	PIN NO.	DIM.A	DIM.B	DIM.C
4	1.50	6.10	2.57	23	11.00	15.60	12.07	42	20.50	25.10	21.57
5	2.00	6.60	3.07	24	11.50	16.10	12.57	43	21.00	25.60	22.07
6	2.50	7.10	3.57	25	12.00	16.60	13.07	44	21.50	26.10	22.57
7	3.00	7.60	4.07	26	12.50	17.10	13.57	45	22.00	26.60	23.07
8	3.50	8.10	4.57	27	13.00	17.60	14.07	46	22.50	27.10	23.57
9	4.00	8.60	5.07	28	13.50	18.10	14.57	47	23.00	27.60	24.07
10	4.50	9.10	5.57	29	14.00	18.60	15.07	48	23.50	28.10	24.57
11	5.00	9.60	6.07	30	14.50	19.10	15.57	49	24.00	28.60	25.07
12	5.50	10.10	6.57	31	15.00	19.60	16.07	50	24.50	29.10	25.57
13	6.00	10.60	7.07	32	15.50	20.10	16.57	51	25.00	29.60	26.07
14	6.50	11.10	7.57	33	16.00	20.60	17.07	52	25.50	30.10	26.57
15	7.00	11.60	8.07	34	16.50	21.10	17.57	53	26.00	30.60	27.07
16	7.50	12.10	8.57	35	17.00	21.60	18.07	54	26.50	31.10	27.57
17	8.00	12.60	9.07	36	17.50	22.10	18.57	55	27.00	31.60	28.07
18	8.50	13.10	9.57	37	18.00	22.60	19.07	56	27.50	32.10	28.57
19	9.00	13.60	10.07	38	18.50	23.10	19.57	57	28.00	32.60	29.07
20	9.50	14.10	10.57	39	19.00	23.60	20.07	58	28.50	33.10	29.57
21	10.00	14.60	11.07	40	19.50	24.10	20.57	59	29.00	33.60	30.07
22	10.50	15.10	11.57	41	20.00	24.60	21.07	60	29.50	34.10	30.57
65	32.00	36.60	33.07	68	33.50	38.10	34.57				



APPLICABLE FFC





RECOMMEND PCB LAYOUT
TOLERANCE:±0.05

REV	ECO NO	DESCRIPTION OF REVISIONS	SIGN	DATE		
					Material	See note
					Mould No.	
					Packing Qty.	
					Circuit No.	6~60pin

RoHS Compliant	Halogen - Free

TOLERANCE UNLESS SPECIFIED
LINEAR
.X ±0.3
.XX ±0.2
.XXX ±0.1
ANGLE ±5°

SIZE	A4
SHEET	1/1
SCALE	8/1
UNIT	mm

Swiclick

REVISION A

TITLE: FPC 0.5Pitch 1.5H ZIF R/A Down Contact Connector

DRAWING NO. GYFA0515-XXRD-G

APPROVED	CHECKED	DRAWN





NOTES:

1.10 Sprocket hole pitch sumulative tolerance ±0.20.
2.Carrier camber is within 1mm in 100mm.
3.Material: transparent conductive polystyrene alloy.
4.All dimensions meet EIA-481-3 requirements.
5.For tape width (dimension A) 16 and 24mm a pilot hole is provided on one side.
For tape width(dimension A)32 and 44 and 56mm pilot holes are provided on both sides.







DESCRIPTION	0.5/1.0mm Pitch FPC CONNECTOR				
0.5mm Series PIN NO.	04Pin ~ 06Pin	07Pin ~ 22Pin	23Pin ~ 30Pin	31Pin ~ 54Pin	55Pin ~ 61Pin
1.0mm Series PIN NO.		04Pin ~ 10Pin	11Pin ~ 14Pin	15Pin ~ 26Pin	27Pin ~ 30Pin
DIM: W	16	24	32	44	56
DIM: W1			28.4	40.4	52.4
DIM: W2	7.5	11.5	14.2	20.2	26.2
PCS/REEL	4,000				
REEL/BOX	15	10	8	6	5
BOX (PCS)	60,000	40,000	32,000	24,000	20,000
CTN SIZE	340*340*320				

Swiclick

GENERAL TOLERANG UNLESS OTHERWISE SPECIFIED		PART NO: GYFA0515-XXRD-G
X.X	±0.20	
X.XX	±0.10	TITLE: 0.5/1.0 ZIF FPC SMT R/A EMBOSSED TAPE PACKING
X.XXX		
ANG.	1	

Swiclick

APPROVAL SPECIFICATIONS

Product name	P/N	Version	Document No.	Page
FPC Connector	GYFA0515-XXRD-G	A/00		11/13

7、操作指示 Instruction upon usage

步骤 1: Joining step 1： 使用拇指或食指，将上盖往上掀开。 Use the thumb or the forefinger, raise the top cover up.	
步骤 2: Joining step 2： FPC 导电处朝下，平行的插入连接器中。 FPC gets along with conductivly down. The parallel one inserts it in the connector .	
步骤 3: Joining step 3： 轻压上盖中间往下旋转至定位，直到 FPC 完全插入且没有移动。 Press the top cover lightly and rotate down to make a reservation , until FPC is totally inserted and not moved .	
步骤 4: Joining step 4： FPC removal FPC 退出 小心掀起上盖，将 FPC 退出. Lift the top cover carefully, withdraw FPC from .	
警告 Warning!! 旋转的角度不可大于 135 度。 The whirling angle can't be greater than 135 degrees.	

Swiclick

APPROVAL SPECIFICATIONS

Product name	P/N	Version	Document No.	Page
FPC Connector	GYFA0515-XXRD-G	A/00		12/13

警告 Warning!! 当 FPC 插入的角度偏斜时，可能会引起导通不良。 When the angle that FPC inserts in is askew, may cause and lead openly and badly .	
警告 Warning!! 当 FPC 插入的角度偏斜时，可能会引起导通不良。 When the angle that FPC inserts in is askew, may cause and lead openly and badly .	
警告 Warning!! 向上拉扯的力量不要超过 0.05N/pin max. The strength of dragging upwards don't exceed 0.05N/pin max .	
警告 Warning!! 开启连接器掀盖时，不要使用过度的力量及避免接触到端子。 covering , don't use excessive strength and avoid touching the end son .	
警告 Warning!! 当在开启 FPC 时，不要使用过度的力量及避免接触到端子。 Don't use excessive strength and avoid touching the end son when open FPC.	

APPROVAL SPECIFICATIONS

Product name	P/N	Version	Document No.	Page
FPC Connector	GYFA0515-XXRD-G	A/00		13/13

警告 Warning!! 施压的力量，应该要平均. The strength of exerting pressure should be average. 如图所示，不要试着做移动或重新确定盖子位置。 As illustrated, do not attempt removal or re-positioning of the actuator.	
警告 Warning!! 掀盖的面积，应该要平均. Lift the area overlayed, should be average. 如图所示, 不要试着做移动或重新确定盖子的位置。 As illustrated, do not attempt removal or re-positioning of the actuator.	
警告 Warning!! PCB 板平整度必须在 0.1mm max. The roughness of PCB board must be in 0.1mm max.